



Dimensions:mm

- A:12.6 ± 0.2
- B:13.8(Max)
- C:5.0(Max)
- D:6.0 ± 0.2
- E:2.5 ± 0.1
- F:2.0 ± 0.5
- G:4.0 ± 0.5
- H:+0.15/-0

## Electrical characteristics

	Inductance μH ± 20% @ 0A	DCR (mΩ)Max	Saturation Current A(Max)	Temperature Rise Current A(Max)
NBMC1350N-R36M	0.36	1.1	75.0	41.0
NBMC1350N-R47M	0.47	1.3	65.0	38.0
NBMC1350N-R50M	0.50	1.5	55.0	36.0
NBMC1350N-R56M	0.56	1.5	55.0	36.0
NBMC1350N-R62M	0.62	1.7	54.0	34.0
NBMC1350N-1R0M	1.00	2.5	50.0	29.0
NBMC1350N-1R2M	1.20	3.0	49.0	25.0
NBMC1350N-1R5M	1.50	4.1	48.0	23.0
NBMC1350N-2R2M	2.20	5.5	32.0	20.0
NBMC1350N-3R3M	3.30	9.2	32.0	15.0
NBMC1350N-4R7M	4.70	15.0	27.0	12.0
NBMC1350N-6R8M	6.80	18.5	21.0	11.0