



Dimensions:mm
 A: 10.0 ± 0.5
 B: 9.0 ± 0.5
 C: 4.0 ± 0.5
 D:2.1 (REF)

Electrical characteristics

Part No.	Inductance	TESTING	DC	RATED DC
	L (uH)	FREQ (KHZ)	RESISTANCE (OHM)Max	CURRENT (A)Max
CD104N-100□	10	200	0.053	2.38
CD104N-120□	12	200	0.061	2.13
CD104N-150□	15	200	0.070	1.87
CD104N-180□	18	200	0.081	1.73
CD104N-220□	22	200	0.088	1.60
CD104N-270□	27	200	0.100	1.44
CD104N-330□	33	200	0.120	1.26
CD104N-390□	39	200	0.151	1.20
CD104N-470□	47	200	0.170	1.10
CD104N-560□	56	200	0.199	1.01
CD104N-680□	68	200	0.223	0.91
CD104N-820□	82	200	0.252	0.85
CD104N-101□	100	200	0.344	0.74
CD104N-121□	120	200	0.396	0.69
CD104N-151□	150	200	0.544	0.61
CD104N-181□	180	200	0.621	0.56
CD104N-221□	220	200	0.721	0.53
CD104N-271□	270	200	0.949	0.45
CD104N-331□	330	200	1.100	0.42
CD104N-391□	390	200	1.245	0.38
CD104N-471□	470	200	1.526	0.35
CD104N-561□	560	200	1.904	0.32

□:J=5% K=10% M=20%