



Dimensions:mm

A:10.0 ± 0.5

B:9.5 ± 0.5

C:5.5 ± 0.5

D:2.1 (REF)

Electrical characteristics

Part No.	Inductance	TESTING	DC	RATED DC
	L (uH)	FREQ (KHZ)	RESISTANCE (OHM)Max	CURRENT (A)Max
CD105N-100□	10	200	0.060	2.60
CD105N-120□	12	200	0.070	2.45
CD105N-150□	15	200	0.080	2.27
CD105N-180□	18	200	0.090	2.15
CD105N-220□	22	200	0.100	1.95
CD105N-270□	27	200	0.110	1.76
CD105N-330□	33	200	0.120	1.50
CD105N-390□	39	200	0.140	1.37
CD105N-470□	47	200	0.170	1.28
CD105N-560□	56	200	0.190	1.17
CD105N-680□	68	200	0.220	1.11
CD105N-820□	82	200	0.250	1.00
CD105N-101□	100	200	0.350	0.97
CD105N-121□	120	200	0.400	0.89
CD105N-151□	150	200	0.470	0.78
CD105N-181□	180	200	0.63	0.72
CD105N-221□	220	200	0.73	0.66
CD105N-271□	270	200	0.97	0.57
CD105N-331□	330	200	1.15	0.52
CD105N-391□	390	200	1.30	0.48
CD105N-471□	470	200	1.48	0.42
CD105N-561□	560	200	1.90	0.33
CD105N-681□	680	200	2.25	0.28
CD105N-821□	820	200	2.55	0.24

□:J=5% K=10% M=20%