



Dimensions:mm

A:7.8 ± 0.5

B:7.0 ± 0.5

C:3.5 ± 0.5

D:2.1 (REF)

Electrical characteristics

Part No.	Inductance	TESTING	DC	RATED DC
	L (uH)	FREQ (KHZ)	RESISTANCE (OHM)Max	CURRENT (A)Max
CD73N-221□	220	200	1.57	0.35
CD73N-100□	10	200	0.08	1.44
CD73N-120□	12	200	0.09	1.39
CD73N-150□	15	200	0.10	1.24
CD73N-180□	18	200	0.11	1.12
CD73N-220□	22	200	0.13	1.07
CD73N-270□	27	200	0.15	0.94
CD73N-330□	33	200	0.17	0.85
CD73N-390□	39	200	0.22	0.74
CD73N-470□	47	200	0.25	0.68
CD73N-560□	56	200	0.28	0.64
CD73N-680□	68	200	0.33	0.59
CD73N-820□	82	200	0.41	0.54
CD73N-101□	100	200	0.48	0.51
CD73N-121□	120	200	0.54	0.49
CD73N-151□	150	200	0.75	0.40
CD73N-181□	180	200	1.02	0.36
CD73N-221□	220	200	1.20	0.31
CD73N-271□	270	200	1.31	0.29
CD73N-331□	330	200	1.50	0.28

□:J=5% K=10% M=20%