



Dimensions:mm

A: 7.8 ± 0.5

B: 7.0 ± 0.5

C: 5.0 ± 0.5

D:2.1 (REF)

Electrical characteristics

Part No.	Inductance	TESTING	DC	RATED DC
	L (uH)	FREQ (KHZ)	RESISTANCE (OHM)Max	CURRENT (A)Max
CD75N-100□	10	200	0.07	2.30
CD75N-120□	12	200	0.08	2.00
CD75N-150□	15	200	0.09	1.80
CD75N-180□	18	200	0.10	1.60
CD75N-220□	22	200	0.11	1.50
CD75N-270□	27	200	0.12	1.30
CD75N-330□	33	200	0.13	1.20
CD75N-390□	39	200	0.16	1.10
CD75N-470□	47	200	0.18	1.10
CD75N-560□	56	200	0.24	0.94
CD75N-680□	68	200	0.28	0.85
CD75N-820□	82	200	0.37	0.78
CD75N-101□	100	200	0.43	0.72
CD75N-121□	120	200	0.47	0.66
CD75N-151□	150	200	0.64	0.56
CD75N-181□	180	200	0.71	0.51
CD75N-221□	220	200	0.96	0.49
CD75N-271□	270	200	1.11	0.42
CD75N-331□	330	200	1.26	0.40
CD75N-391□	390	200	1.77	0.36
CD75N-471□	470	200	1.96	0.34

□:J=5% K=10% M=20%