



Dimensions:mm

A:4.0 (Max)

B:4.0 (Max)

C:1.4 (Max)

D:5.2 (Max)

E:Ø2.8 (REF)

F:1.10(REF)

Electrical characteristics

Part No.	Inductance	TESTING	DC	RATED DC	
	L	FREQ	RESISTANCE	CURRENT (A)Max	
	(uH)	(KHZ)	(OHM)Max	Isat	Irms
CDH3D11N-2R7□	2.7	200	0.0747	0.53	1.82
CDH3D11N-4R7□	4.7	200	0.1092	0.40	1.38
CDH3D11N-6R8□	6.8	200	0.1725	0.34	1.05
CDH3D11N-8R2□	8.2	200	0.2185	0.32	0.95
CDH3D11N-100□	10.0	200	0.2300	0.28	0.90
CDH3D11N-120□	12.0	200	0.2645	0.25	0.81
CDH3D11N-150□	15.0	200	0.3680	0.23	0.68
CDH3D11N-180□	18.0	200	0.4600	0.21	0.58
CDH3D11N-220□	22.0	200	0.5175	0.19	0.53
CDH3D11N-270□	27.0	200	0.7475	0.17	0.48
CDH3D11N-330□	33.0	200	0.8050	0.15	0.41
CDH3D11N-390□	39.0	200	0.9775	0.14	0.40

□:M=±20% P=±30%