



Dimensions:mm

A:  $7.8 \pm 0.5$

B:  $7.2 \pm 0.5$

C:  $5.0 \pm 0.5$

## Electrical characteristics

Part No.	Inductance	TESTING	DC	RATED DC
	L (uH)	FREQ (KHZ)	RESISTANCE (OHM)Max	CURRENT (A)Max
CDR074N-100□	10.0	200	0.07	1.65
CDR074N-120□	12.0	200	0.07	1.57
CDR074N-150□	15.0	200	0.08	1.39
CDR074N-180□	18.0	200	0.10	1.29
CDR074N-220□	22.0	200	0.13	1.12
CDR074N-270□	27.0	200	0.16	1.06
CDR074N-330□	33.0	200	0.18	0.97
CDR074N-390□	39.0	200	0.18	0.91
CDR074N-470□	47.0	200	0.27	0.80
CDR074N-560□	56.0	200	0.29	0.76
CDR074N-680□	68.0	200	0.33	0.68
CDR074N-820□	82.0	200	0.43	0.62
CDR074N-101□	100.0	200	0.49	0.55
CDR074N-121□	120.0	200	0.68	0.49
CDR074N-151□	150.0	200	0.94	0.44
CDR074N-181□	180.0	200	1.00	0.40
CDR074N-221□	220	200	1.18	0.36
CDR074N-271□	270	200	1.30	0.33

□: M=±20% P=±30%