



Dimensions:mm

A:7.3 ± 0.5

B:7.3 ± 0.5

C:4.5 (Max)

D:5.2 ± 0.3

E:2.0 ± 0.2

Electrical characteristics

Part No.	Inductance L (uH)	TESTING FREQ (KHZ)	DC RESISTANCE (OHM)Max	RATED DC CURRENT (A)Max
CDRH074N-100□	10	200	49m	1.84
CDRH074N-120□	12	200	58m	1.71
CDRH074N-150□	15	200	81m	0.47
CDRH074N-180□	18	200	91m	1.31
CDRH074N-220□	22	200	0.11	1.23
CDRH074N-270□	27	200	0.15	1.12
CDRH074N-330□	33	200	0.17	0.96
CDRH074N-390□	39	200	0.23	0.91
CDRH074N-470□	47	200	0.26	0.88
CDRH074N-560□	56	200	0.35	0.75
CDRH074N-680□	68	200	0.38	0.69
CDRH074N-820□	82	200	0.43	0.61
CDRH074N-101□	100	200	0.61	0.60
CDRH074N-121□	120	200	0.66	0.52
CDRH074N-151□	150	200	0.88	0.46
CDRH074N-181□	180	200	0.98	0.42
CDRH074N-221□	220	200	1.17	0.36
CDRH074N-271□	270	200	1.64	0.34
CDRH074N-331□	330	200	1.86	0.32
CDRH074N-391□	390	200	2.85	0.29
CDRH074N-471□	470	200	3.01	0.26
CDRH074N-561□	560	200	3.62	0.23
CDRH074N-681□	680	200	4.630	0.22
CDRH074N-821□	820	200	5.200	0.20
CDRH074N-102□	1000	200	6.000	0.18

□:K=±10% M=±20% P=±30%