



Dimensions:mm

A:12.0± 0.5

B:12.0± 0.5

C:4.5 ± 0.5

Electrical characteristics

Part No.	Inductance	TESTING	DC	RATED DC CURRENT (A)Max
	L (uH)	FREQ (KHZ)	RESISTANCE (OHM)Max	
CDRH124N-3R9□	3.9	200	0.015	6.50
CDRH124N-4R7□	4.7	200	0.018	5.70
CDRH124N-6R8□	6.8	200	0.023	4.90
CDRH124N-8R2□	8.2	200	0.026	4.60
CDRH124N-100□	10	200	0.028	4.50
CDRH124N-120□	12	200	0.038	4.00
CDRH124N-150□	15	200	0.050	3.20
CDRH124N-180□	18	200	0.057	3.10
CDRH124N-220□	22	200	0.066	2.90
CDRH124N-270□	27	200	0.080	2.80
CDRH124N-330□	33	200	0.097	2.70
CDRH124N-390□	39	200	0.132	2.10
CDRH124N-470□	47	200	0.160	1.90
CDRH124N-560□	56	200	0.190	1.80
CDRH124N-680□	68	200	0.220	1.50
CDRH124N-820□	82	200	0.260	1.30
CDRH124N-101□	100	200	0.308	1.20
CDRH124N-121□	120	200	0.380	1.10
CDRH124N-151□	150	200	0.530	0.95
CDRH124N-181□	180	200	0.620	0.85
CDRH124N-221□	220	200	0.700	0.80
CDRH124N-271□	270	200	0.870	0.60
CDRH124N-331□	330	200	0.990	0.50

□:K=±10% M=±20% P=±30%