



Dimensions:mm

A:12.0± 0.5

B:12.0± 0.5

C:6.0 (Max)

Electrical characteristics

| Part No. | Inductance L (uH) | TESTING FREQ (KHZ) | DC RESISTANCE (OHM)Max | RATED DC CURRENT (A)Max |
|----------------|-------------------------|--------------------------|------------------------------|-------------------------------|
| CDRH125N--100□ | 10 | 200 | 0.025 | 4.00 |
| CDRH125N--120□ | 12 | 200 | 0.027 | 3.50 |
| CDRH125N--150□ | 15 | 200 | 0.030 | 3.30 |
| CDRH125N--180□ | 18 | 200 | 0.034 | 3.00 |
| CDRH125N--220□ | 22 | 200 | 0.036 | 2.80 |
| CDRH125N--270□ | 27 | 200 | 0.051 | 2.30 |
| CDRH125N--330□ | 33 | 200 | 0.057 | 2.10 |
| CDRH125N--390□ | 39 | 200 | 0.068 | 2.00 |
| CDRH125N--470□ | 47 | 200 | 0.075 | 1.80 |
| CDRH125N--560□ | 56 | 200 | 0.110 | 1.70 |
| CDRH125N--680□ | 68 | 200 | 0.120 | 1.50 |
| CDRH125N--820□ | 82 | 200 | 0.140 | 1.40 |
| CDRH125N--101□ | 100 | 200 | 0.160 | 1.30 |
| CDRH125N--121□ | 120 | 200 | 0.170 | 1.10 |
| CDRH125N--151□ | 150 | 200 | 0.230 | 1.00 |
| CDRH125N--181□ | 180 | 200 | 0.290 | 0.90 |
| CDRH125N--221□ | 220 | 200 | 0.400 | 0.80 |
| CDRH125N--271□ | 270 | 200 | 0.460 | 0.75 |
| CDRH125N--331□ | 330 | 200 | 0.510 | 0.68 |
| CDRH125N--391□ | 390 | 200 | 0.690 | 0.65 |
| CDRH125N--471□ | 470 | 200 | 0.770 | 0.58 |
| CDRH125N-561□ | 560 | 200 | 0.860 | 0.54 |
| CDRH125N-681□ | 680 | 200 | 1.200 | 0.56 |
| CDRH125N-821□ | 820 | 200 | 1.340 | 0.43 |
| CDRH125N-102□ | 1000 | 200 | 1.530 | 0.40 |

□:K=±10% M=±20% P=±30%