



Dimensions:mm

A: 7.6 ± 0.3

B: 10.0 ± 0.3

C:3.5 (REF)

D: 7.6 ± 0.3

E: 2.5 ± 0.3

F: 1.4 ± 0.3

G: 4.55 ± 0.3

Electrical characteristics

Part No.	Inductance	TESTING		DC	RATED DC
	L (uH)	FREQ (KHZ)	RESISTANCE (OHM)Max	CURRENT (A)Max	
SD073N-1R0□	1.0	200	19m	3.12	
SD073N-1R5□	1.5	200	23m	2.85	
SD073N-2R2□	2.2	200	28m	2.66	
SD073N-3R3□	3.3	200	35m	2.26	
SD073N-4R7□	4.7	200	43m	1.96	
SD073N-6R8□	6.8	200	55m	1.76	
SD073N-100□	10	200	80m	1.34	
SD073N-120□	12	200	90m	1.23	
SD073N-150□	15	200	0.12	1.09	
SD073N-180□	15	200	0.13	0.99	
SD073N-220□	22	200	0.15	0.90	
SD073N-270□	27	200	0.21	0.81	
SD073N-330□	33	200	0.25	0.72	
SD073N-390□	39	200	0.31	0.67	
SD073N-470□	47	200	0.35	0.60	
SD073N-560□	56	200	0.43	0.55	
SD073N-680□	68	200	0.52	0.50	
SD073N-820□	82	200	0.60	0.46	
SD073N-101□	100	200	0.79	0.41	

□: M=±20% P=±30%