



Dimensions:mm

A:13.0 (Max)

B:9.5 (Max)

C:5.46 (Max)

D:2.54 ± 0.3

E:2.54 ± 0.3

F:7.62 ± 0.3

## Electrical characteristics

Part No.	Inductance	TESTING	DC	RATED DC
	L (uH)	FREQ (KHZ)	RESISTANCE (OHM)Max	CURRENT (A)Max
SL0804N-1R0M	1.0	200	0.009	9.00
SL0804N-1R5M	1.5	200	0.010	8.00
SL0804N-2R2M	2.2	200	0.012	7.00
SL0804N-3R3M	3.3	200	0.015	6.40
SL0804N-4R7M	4.7	200	0.018	5.40
SL0804N-6R8M	6.8	200	0.027	4.60
SL0804N-100M	10.0	200	0.038	3.80
SL0804N-150M	15.0	200	0.046	3.00
SL0804N-220M	22.0	200	0.085	2.60
SL0804N-330M	33.0	200	0.100	2.00
SL0804N-470M	47.0	200	0.140	1.60
SL0804N-680M	68.0	200	0.200	1.40
SL0804N-101M	100.0	200	0.280	1.20
SL0804N-151M	150.0	200	0.400	1.00
SL0804N-221M	220.0	200	0.610	0.80
SL0804N-331M	330.0	200	1.020	0.60
SL0804N-471M	470.0	200	1.270	0.50
SL0804N-681M	680.0	200	2.020	0.40
SL0804N-102M	1000.0	200	3.000	0.30