



Electrical characteristics

Part No.	Inductance	TESTING	DC	RATED DC
	L (uH)	FREQ (KHZ)	RESISTANCE (OHM)Max	CURRENT (A)Max
SL1306N-1R0M	1.0	200	0.009	20.00
SL1306N-2R2M	2.2	200	0.014	16.00
SL1306N-3R3M	3.3	200	0.015	14.00
SL1306N-4R7M	4.7	200	0.020	12.00
SL1306N-5R6M	5.6	200	0.020	12.00
SL1306N-6R8M	6.8	200	0.023	11.00
SL1306N-100M	10.0	200	0.031	10.00
SL1306N-150M	15.0	200	0.036	8.00
SL1306N-220M	22.0	200	0.047	7.00
SL1306N-330M	33.0	200	0.066	5.50
SL1306N-470M	47.0	200	0.086	4.50
SL1306N-680M	68.0	200	0.130	3.50
SL1306N-101M	100.0	200	0.190	3.00
SL1306N-151M	150.0	200	0.250	2.60
SL1306N-221M	220.0	200	0.380	2.40
SL1306N-331M	330.0	200	0.560	1.90
SL1306N-471M	470.0	200	0.850	1.40
SL1306N-681M	680.0	200	1.100	1.20
SL1306N-102M	1000.0	200	1.800	1.00