



Dimensions:mm

A:13.0 (Max)

B:9.50 (Max)

C:5.21 (Max)

D:2.54 ± 0.5

E:2.54 ± 0.5

F:7.62 ± 0.5

Electrical characteristics

Part No.	Inductance	TESTING	DC	RATED DC
	L (uH)	FREQ (KHZ)	RESISTANCE (OHM)Max	CURRENT (A)Max
SS0804N-1R0M	1.0	200	0.021	5.60
SS0804N-1R5M	1.5	200	0.022	5.20
SS0804N-2R2M	2.2	200	0.032	5.00
SS0804N-3R3M	3.3	200	0.039	3.90
SS0804N-4R7M	4.7	200	0.054	3.20
SS0804N-6R8M	6.8	200	0.075	2.80
SS0804N-100M	10	200	0.101	2.40
SS0804N-150M	15	200	0.150	2.00
SS0804N-220M	22	200	0.207	1.60
SS0804N-330M	33	200	0.334	1.40
SS0804N-470M	47	200	0.472	1.00
SS0804N-680M	68	200	0.660	0.90
SS0804N-101M	100	200	0.924	0.80
SS0804N-151M	150	200	1.290	0.40
SS0804N-221M	220	200	1.800	0.60
SS0804N-331M	330	200	2.500	0.50
SS0804N-471M	470	200	3.000	0.40
SS0804N-681M	680	200	4.200	0.30
SS0804N-102M	1000	200	5.900	0.20