



Dimensions:mm

A:1.6 ± 0.2

B:0.8 ± 0.2

C:0.8 ± 0.2

D:0.4 ± 0.2

Electrical characteristics

Part No.	TEST FREQUENCY (MHz)	IMPEDANCE (Ω)	DC RESISTANCE (Ω)Max	RATE CURRENT (MA)Max
CB160808N-110	100	11±25%	0.05	500
CB160808N-190	100	19±25%	0.08	500
CB160808N-220	100	22±25%	0.10	400
CB160808N-300	100	30±25%	0.10	400
CB160808N-320	100	32±25%	0.10	400
CB160808N-400	100	40±25%	0.10	400
CB160808N-470	100	47±25%	0.10	300
CB160808N-600	100	60±25%	0.10	300
CB160808N-750	100	75±25%	0.15	300
CB160808N-800	100	80±25%	0.15	300
CB160808N-121	100	120±25%	0.25	300
CB160808N-151	100	150±25%	0.30	200
CB160808N-221	100	220±25%	0.30	200
CB160808N-301	100	300±25%	0.40	200
CB160808N-451	100	450±25%	0.50	200
CB160808N-601	100	600±25%	0.50	200
CB160808N-751	100	750±25%	0.70	200
CB160808N-102	100	1000±25%	0.70	200
CB160808N-152	100	1500±25%	1.00	50
CB160808N-222	100	2200±25%	1.20	50